


Enregistrement automatique des agents Zabbix

Ajouter les agents Zabbix automatiquement

Pour ajouter les VM avec agent, on crée une action d'enregistrement automatique sur Zabbix.



Puis en à gauche puis Auto-registration.

On ajoute.

Action **Operations 3**

* Name

Type of calculation A and B

Conditions	Label	Name	Action
	A	Proxy equals <i>homelab</i>	Remove
	B	Host metadata contains <i>linux</i>	Remove
	Add		

Enabled

* At least one operation must exist.

Actions

Action **Operations 3**

Operations	Details	Action
	Add host	Edit Remove
	Add to host groups: LAN Maison, Linux servers	Edit Remove
	Link to templates: Linux by Zabbix agent	Edit Remove
	Add	

* At least one operation must exist.

On clique sur Add.

Du côté des agents, on rajoute "linux" dans Hostmetadata.

```
GNU nano 4.8 /etc/zabbix/zabbix_agentd.conf Modified
#
# Mandatory: no
# Default:
# Hostname=

Hostname=pi-hole

### Option: HostnameItem
# Item used for generating Hostname if it is undefined. Ignored if Hostname is defined.
# Does not support UserParameters or aliases.
#
# Mandatory: no
# Default:
# HostnameItem=system.hostname

### Option: HostMetadata
# Optional parameter that defines host metadata.
# Host metadata is used at host auto-registration process.
# An agent will issue an error and not start if the value is over limit of 255 characters.
# If not defined, value will be acquired from HostMetadataItem.
#
# Mandatory: no
# Range: 0-255 characters
# Default:
ostMetadata=linux
```

On redémarre l'agent.

Revision #1

Created 21 March 2021 17:32:41 by Khroners

Updated 5 July 2021 16:20:23 by Khroners